



# SERITEC® STANDARD

SERITEC® STANDARD range of squeegees has been developed - thanks to the great experience of all Tecno's crew - to satisfy all screen printing industry demands.

STANDARD formulation is suitable for manual and automatic printing. It is resistant to water based inks, Plastisol and common solvents.

## MAIN FEATURES:

- Resistance to abrasion
- Optimal resistance to water-based and Plastisol inks
- Resistance to common solvents
- Suggested for manual and semi-automatic printing

- LOW SWELLING
- LONG LIFE
- GOOD PERFORMANCE

SERITEC® STANDARD squeegees are available with the following features:

**HARDNESS:** from 50 Sh A to 95 Sh A, in standard colours

**SPECIAL SQUEEGEES:** double and triple layer, 9x9, 9.5x9.5, 10x10 SQUARE PROFILE

**LENGTH:** mm 3660, mm 3050 or cut to size

**WIDTH:** from 20 mm up to 100 mm

**THICKNESS:** from 4 mm up to 10 mm

**PROFILE:** P0, P1, P2, P3, P4, P5, P5A, P6



Widely used in garment and textile printing, SERITEC® STANDARD has been tested directly by screen printers, in different printing fields: the excellent feedbacks confirm the already positive results we obtain in chemical lab tests. Suggested for printing on ceramics, fabrics, balloons, and glass.



## TECNO SRL

Strada Borgaretto, 30/2 - 10092 Beinasco (TO) Italy

Phone: +39 011 3584930 - Fax: + 39 011 3580723

info@tecnoitaly.com - www.tecnoitaly.com