



SERITEC® UV

SERITEC® UV has been specially conceived to be highly resistant to UV and Vinylic inks: its special formulation increases the squeegee's capability to withstand chemical aggression of UV inks.

MAIN FEATURES:

- Resistance to abrasion
- Optimal resistance to UV and Vinylic inks
- Resistance to aggressive solvents
- Suggested for semi- and automatic printing

- LOW SWELLING
- RESISTANCE TO UV INKS
- GOOD PERFORMANCE

SERITEC® UV squeegees are available with the following features:

HARDNESS: from 50 sh A to 95 sh A

SPECIAL SQUEEGEES: double and triple layer, 9x9, 9.5x9.5, 10x10 SQUARE PROFILE

LENGTH: mm 3660, mm 3050 or cut to size

WIDTH: from 20 mm up to 100 mm

THICKNESS: from mm 4 up to mm 10

PROFILE: P0, P1, P2, P3, P4, P5, P5A, P6, P7



Main fields of application: plastic processing, glass decoration, optical media, graphic industry and label printing, PVC, metal, polyethylene, foil, polystyrene, PP, ABS, PVC, paper.



TECNO SRL

Strada Borgaretto, 30/2 - 10092 Beinasco (TO) Italy
Phone: +39 011 3584930 - Fax: + 39 011 3580723
info@tecnoitaly.com - www.tecnoitaly.com

